



SUPERIORITY IN EVERY DETAIL

U130=12.9

UXY8

Unbrako[®]

BUILT FOR LIFE

Unbrako Range

Type	Short Description	Designation	Grade
	Unbrako® Socket Head Cap Screws U130 DIN 912 Hardness 12.9 are available in dimension range M1.6 to M42 and in Inch form to BS and ASA Standard from No. 0 to 1" in UNC/UNF and BSW threads	ISO 4762 DIN 912 BS 2470 Series 1936 ASA B 18.3 Series 1960	12.9
	Unbrako® Low head Socket Cap Screws – hardness 10.9 – are available in dimension range from M4 to M20. Conform dimensionally to the Low Head standards DIN 6912 and DIN 7984	UFK	10.9
	Unbrako® socket head countersunk screws are available in dimension range M3 to M24 and in inch form to British Standard form No.4 to 3/4" in UNC/UNF and BSW threads	ISO 10642 DIN 7991 BS 2470	10.9
	Unbrako® button (dome) head socket screws are available in dimension range M3 to M24 and in inch form to British Standard from No.4 to 3/4" in UNC/UNF and BSW threads	ISO 7380 ULS	10.9
	Unbrako® flanged button head socket screws are available in dimension range M3 to M10. Allow covering of large diameter holes. Can be used with softer materials	ULF	10.9
	Unbrako® socket head shoulder screws – hardness 12.9 - are available in dimension range M5 to M20 and in inch form to British Standard from 1/4" to 3/4" in UNC and BSW threads. The shoulder is ground to h8 tolerances.	UPS BS 2470	12.9
	Unbrako® T-Bolts – hardness 12.9 – are available in dimension range M8 to M24 and in inch form from 3/8" to 3/4" in BSW threads. For use with T-Slots to DIN 650.	UTS	12.9
	Unbrako® socket set screws from DIN 913 to 916 and knurled cup are available in dimension range M3 to M24 and in inch form from No.4 to 3/4" in UNC/UNF and BSW threads	DIN 913, 914 915, 916 DIN 916 VZR ASA B18.3	Hardness Rc 45 min
	Unbrako® Pressure Plugs with tapered thread - are available to BS and US Standards in dimension range M8 x 1.0 to M22 x 1.5 and from 1/16" to 1/2"	NPTF (Dryseal) PTF (Levl Seal) BSPT	Hardness Rc 35-40
	Unbrako® socket wrenches to DIN 911 are available in dimension range AF 0.7mm to AF 32mm and in inch form from 1/16" to 1" AF	DIN 911 ISO 2936	Hardness Rc 48-54
	Unbrako® Dowel Pins hardened to DIN 6325 standard and ground to M6 tolerances are available in dimension range from 2mm to 20mm and in inch form from 1/8" to 1"	DIN 6325 ANSI B18.8.2	Hardness Rc 60 +/- 2
	Unbrako® self-locking Durlok screws and nuts with serrated flanges in hardness Class 12.9 (screws) and Class 12 (nuts) are available in dimension range M5 to M20	Durlok® Screw Durlok® Nut	12.9 Class 12